

1500 VENT CHECK VALVE

Wager's model 1500 vent check valve is mounted vertically on the deck of a ship. In the open position, the valve allows for required ventilation. During heavy seas, our disc style float rises to a neoprene seat, and prevents water and debris from entering tanks and bulkheads. A 30 x 30 or 1/4" x 1/4" mesh stainless steel screen provides protection from deck fires. It is available in galvanized steel, and stainless steel. Special request are needed for aluminum and bronze. Sizes 1.5"-12" threaded, welded, flanged and metric flange.



SPECIFICATIONS

GALVANIZED STEEL

CONNECTIONS:

- THREADED (1.5" - 6" ONLY)
- BUTTWELD (1.5" - 6" ONLY)
- FLANGED (METRIC AVAILABLE)
- VICTAULIC GROOVE COUPLING

SIZES:

- 1.5", 2", 2.5", 3", 4", 5", 6", 8", 10", 12", 14"

304 STAINLESS STEEL

CONNECTIONS:

- THREADED (1.5" - 6" ONLY)
- BUTTWELD (1.5" - 6" ONLY)
- FLANGED (METRIC AVAILABLE)
- VICTAULIC GROOVE COUPLING

SIZES:

- 1.5", 2", 2.5", 3", 4", 5", 6", 8", 10", 12", 14"

316 STAINLESS STEEL

CONNECTIONS:

- THREADED (1.5" - 6" ONLY)
- BUTTWELD (1.5" - 6" ONLY)
- FLANGED (METRIC AVAILABLE)
- VICTAULIC GROOVE COUPLING

SIZES:

- 1.5", 2", 2.5", 3", 4", 5", 6", 8", 10", 12", 14"

ANODIZED ALUMINUM

CONNECTIONS:

- THREADED (1.5" - 6" ONLY)
- BUTTWELD (1.5" - 6" ONLY)
- FLANGED (METRIC AVAILABLE)
- VICTAULIC GROOVE COUPLING

SIZES:

- 1.5", 2", 2.5", 3", 4", 5", 6", 8", 10", 12", 14"

ABS TYPE APPROVED



WAGER
C O M P A N Y

WWW.WAGERUSA.COM
Toll Free USA: 800-562-7024