

1750

INVERTED VENT CHECK VALVE

Inverted Vent Check Valves protect tanks and bulkheads from pressure build-up during loading and unloading of liquid or dry cargo and assure maximum efficiency during operations. The ball float prevents contamination of the tank cargo by sea water during heavy seas. All steel castings are hot dipped galvanized. All aluminum castings are anodized.



BODY



FLOAT



FLAME
SCREEN



SPACER



PROTECTIVE
MESH



COVER



SPECIFICATIONS

GALVANIZED STEEL

FLOAT MATERIAL:

- 316 STAINLESS STEEL (STANDARD)
- COPPER
- HIGH DENSITY POLYETHYLENE
- MONEL

CONNECTIONS:

- THREADED
- BUTTWELD
- SOCKETWELD
- FLANGED
- VICTAULIC

SIZES:

- .50", .75", 1", 1.25", 1.5", 2", 2.5", 3", 4"

BRONZE

FLOAT MATERIAL:

- 316 STAINLESS STEEL (STANDARD)
- COPPER
- HIGH DENSITY POLYETHYLENE
- MONEL

CONNECTIONS:

- THREADED
- FLANGED
- SIL-BRAZED
- VICTAULIC

SIZES:

- .50", .75", 1", 1.25", 1.5", 2", 2.5", 3", 4"

STAINLESS STEEL

FLOAT MATERIAL:

- 316 STAINLESS STEEL (STANDARD)
- COPPER
- HIGH DENSITY POLYETHYLENE
- MONEL

CONNECTIONS:

- THREADED
- BUTTWELD
- SOCKETWELD
- FLANGED
- VICTAULIC

SIZES:

- .50", .75", 1", 1.25", 1.5", 2", 2.5", 3", 4"

ANODIZED ALUMINUM

FLOAT MATERIAL:

- 316 STAINLESS STEEL (STANDARD)
- COPPER
- HIGH DENSITY POLYETHYLENE
- MONEL

CONNECTIONS:

- THREADED
- BUTTWELD
- SOCKETWELD
- FLANGED
- VICTAULIC

SIZES:

- .50", .75", 1", 1.25", 1.5", 2", 2.5", 3", 4"

ABS TYPE APPROVED



WAGER
COMPANY

WWW.WAGERUSA.COM
Toll Free USA: 800-562-7024